



ProShift MP Auto Trans Fluid

DESCRIPTION

ProShift Multi-Purpose Automotive Transmission Fluid is a premium lubricant designed and recommended for use in automatic transmissions previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands.

ProShift Multi-Purpose Auto Trans Fluid’s advanced additive technology and balanced friction modifiers provide long-term protection and optimum performance for automatic transmissions found in passenger cars, sports utility vehicles and light trucks. Due to excellent low-temperature fluidity and red product color, it also delivers excellent hydraulic performance in industrial applications or where leak detection is an important characteristic.

PERFORMANCE BENEFITS

- Superior anti-wear properties protect critical transmission components
- Balanced frictional properties for smooth shifting
- Excellent anti-shudder performance
- Good seal compatibility
- Protection against varnish and sludge formation
- Superior thermal stability
- Outstanding low-temperature fluidity

PRODUCT APPLICATION

ProShift Multi-Purpose Auto Trans Fluid is recommended for the following automatic transmission fluid requirements:

Transmissions previously serviceable by GM DEXRON®-III(H), DEXRON®-III(G), DEXRON®-II(E), DEXRON®-II(D) & DEXRON®-II or Ford MERCON® brands
 Allison C-3 & C-4
 Caterpillar TO-2

Not recommended for use in transmissions requiring GM DEXRON®-VI, Ford MERCON®-V, MERCON® SP & MERCON® LV fluids, or Ford ATF Type F applications.

Typical Physical Properties		
Property	Method	
Viscosity, cSt @ 40°C	D-445	32.9
Viscosity, cSt @ 100°C	D-445	7.0
Viscosity Index	D-2270	180
Specific Gravity @ 60°F	D-1250	0.862
Flash Point, COC, °C(°F)	D-92	204 (399)
Pour Point, °C(°F)	D-97	-51 (-60)
Color	D-1500	Red
Brookfield Viscosity, cP @ -40°C	D-2983	18,000
Minor variations in physical test results may occur through normal manufacturing		

Always consult original equipment manufacturer’s lubricant recommendation for proper fluid application.

